

## Specifications

### Measurement Functions

Sweep channels:	2 channels (reflection characteristics, transmission characteristics)
Reflection characteristics (S <sub>11</sub> ):	Amplitude, Group delay, Chromatic dispersion, Chromatic dispersion slope
Transmission characteristics (S <sub>21</sub> ):	Amplitude, Group delay, Chromatic dispersion, Chromatic dispersion slope, Polarization mode dispersion (OPTQ7760+15, OPTQ7760+15A)

### Optical Signal Source Characteristics<sup>11</sup>

Measurement range:	1525 to 1635nm
Absolute wavelength accuracy <sup>2)</sup> :	±25 pm (standard) ±2 ppm ±1 pm (when used with Q8326)
Wavelength setting resolution:	1 pm
Sweep wavelength range:	Settable from 0.1 to 110 nm (settable from 12.5 GHz to 13.2 THz in optical frequency domain) Set span x (±0.3%) ±30 MHz or less
Sweep repeatability <sup>3)</sup> : Sweep time (measurement time) <sup>4)</sup> :	Approx. 6.7 ms (per measurement point) Approx. 4 s (per sweep span)
Optical output power level <sup>5)</sup> : Optical monitor output power level <sup>6)</sup> :	-15 dBm or more -20 dBm or more

### Amplitude Characteristics

Scale:	Logarithmic table (0.2, 0.5, 1.0, 2.0, 5.0, 10.0 dB/div) and also linear
Modulation frequency range:	40 MHz to 3 GHz
Dynamic range <sup>8)</sup> :	Transmission characteristics; 35 dB (typ. 40 dB) Reflection characteristics; 33 dB (typ. 38 dB)
Linearity <sup>7)</sup> :	±0.10 dB (relative level 0 to -25 dB) ±0.25 dB (relative level -25 to -30 dB)
Polarization dependency:	Transmission characteristics (test port 2); ±0.10 dB Reflection characteristics (test port 1); ±0.15 dB
Repeatability at connector insertion <sup>9)</sup> :	±0.1 dB

### Group Delay Characteristics

Modulation frequency range (fm):	40 MHz to 3 GHz	
Max. measurement range:	7.5 μs	
Group delay resolution:	1.0 fs	
Relative group delay accuracy <sup>7)</sup> :		
Relative level (dB)	Accuracy (s)	for fm=3 GHz
0 to -5 dB	±0.015%/fm	±0.05 ps
-5 to -10 dB	±0.048%/fm	±0.16 ps
-10 to -15 dB	±0.15%/fm	±0.5 ps
-15 to -20 dB	±0.48%/fm	±1.6 ps
-20 to -25 dB	±1.5%/fm	±5 ps

### Chromatic Dispersion

Measurement units:	Wavelength range (ps/nm), Optical frequency range (ps/GHz), Chromatic dispersion slope (ps/nm <sup>2</sup> ), Displays in ps/nm/km, ps/GHz/km, ps/nm <sup>2</sup> /km, and ps/GHz <sup>2</sup> /km are also possible by inputting the length of optical fiber under test
Measurement range:	0.1 ps/nm to 1 μs/nm
Measurement resolution:	0.01 ps/nm

### Fiber Chromatic Dispersion Measurement<sup>9)</sup>

Repeatability of dispersion coefficient measurement:	0.025 ps/nm, 0.003 ps/nm/km
Repeatability of zero dispersion wavelength measurement:	0.030 nm
Repeatability of dispersion slope measurement at zero dispersion wavelength:	0.025 ps/nm <sup>2</sup> , 0.002 ps/nm <sup>2</sup> /km
Accuracy of zero CD wavelength:	±0.080 nm ±0.035 nm (when used with Q8326)
Waveform fitting functions:	Linear fit, Quadratic fit, Three-term sellmeier fit, Five-term sellmeier fit

### Fiber Length Measurement

Range of measurements:	0.2 m to 10,000 km
Resolution:	0.02 mm or 0.01% of the measured length, whichever is greater
Range of inputs for refraction index:	1.000000 to 2.000000

### Polarization Mode Dispersion (OPTQ7760+15, OPTQ7760+15A)

Measurement units:	ps	
	Displays in ps/√km are also possible by inputting the length of optical fiber under test	
Maximum measurement range:	333 ps	
Measurement resolution:	1.0 fs	
Measurement accuracy <sup>7)</sup> :		
Relative level (dB)	Accuracy (s)	for fm=3 GHz
0 to -5 dB	±0.030%/fm	±0.1 ps
-5 to -10 dB	±0.063%/fm	±0.2 ps
-10 to -15 dB	±0.17%/fm	±0.6 ps
-15 to -20 dB	±0.50%/fm	±1.7 ps
-20 to -25 dB	±1.6%/fm	+5.3 ps

### Polarization Control Function (OPTQ7760+15, OPTQ7760+15A)

Polarization extinction ratio:	30 dB or more
Angle setting resolution:	0.1 degree

### Processing Functions

Memory function:	Save measurement data to back-up memory and/or to a floppy disk
Display:	Optical frequency display, Overlay, Dividing into two parts, Cursor function
Computing/analysis:	Averaging, Normalization, Smoothing, Expansion show function, Limit line, Partial waveform fitting functions, Waveform fitting functions (Linear fit, Quadratic fit, Three-term Sellmeier fit, Five-term sellmeier fit)

### Optical Input/Output

Optical connector type <sup>9)</sup> :	FC type connector (standard) Changeable to SC and ST type by using adapters available separately
--	---

### Input/Output Interfaces

GPIB:	IEEE488-1978
Floppy disk drive:	3.5 inch, MS-DOS format
Printer:	D-SUB 25 pin ESC/P, ESC/P-R, PCL
Keyboard:	Conforms to IBM PC-AT
Display:	15 pin, D-SUB connector (VGA)

## General Specifications

<b>Operating environment:</b>	<b>Ambient temperature; 15 to 35°C</b> <b>Relative humidity;</b> <b>85% or less (no condensation)</b>
<b>Storage environment:</b>	<b>Ambient temperature; -10 to 45°C</b> <b>Relative humidity;</b> <b>90% or less (no condensation)</b>
<b>Power:</b>	<b>Display unit; AC 100 to 120 V,</b> <b>AC 220 to 240 V, 50/60 Hz , 300 VA or less</b> <b>Optical network analyzer unit;</b> <b>AC 100 to 120V, AC 220 to 240V, 50/60Hz,</b> <b>310 VA or less</b>
<b>Dimensions:</b>	<b>Display unit;</b> <b>approx. 424 (W) x 220 (H) x 400 (D) mm</b> <b>Optical network analyzer unit;</b> <b>approx. 424 (W) x 220 (H) x 500 (D) mm</b>
<b>Mass:</b>	<b>Display unit; 17 kg or less</b> <b>Optical network analyzer unit; 28 kg or less</b>

## Options (OPTQ7760+15, OPTQ7760+15A)

<b>Polarization mode dispersion measurement</b> <b>(Polarization control function is included)</b>	
<b>At time of order:</b>	<b>OPTQ7760+15</b>
<b>Retrofit option:</b>	<b>OPTQ7760+15A</b>

## Accessories (sold separately)

### Optical connector adapters

<b>FC connector adapter:</b>	<b>A08694</b>
<b>SC connector adapter:</b>	<b>A08695</b>
<b>ST connector adapter:</b>	<b>A08696</b>

- \*1) Warm-up time: 2 hrs.
- \*2) At initial sweep wavelength and at stable temperature.
- \*3) At stable temperature.
- \*4) Excluding internal setting time when set span = 60 GHz
- \*5) At average power. This instrument is a class 1 laser product.
- \*6) Difference between amplitude level and noise level (average value) during direct measurement. At sensitivity = High.
- \*7) Relative level with amplitude level at through measurement as standard.  
No group delay variation under the test sample. At sensitivity = High.
- \*8) Value measured with 10 connector insertions using SMF fiber with FC connector.
- \*9) Under a specific temperature.  
When 11 km dispersion shift fiber was measured for 20 times.  
With zero dispersion wavelength as the center wavelength, measured wavelength span = 10 nm, stepped sweep measurement = 11 points (1 point/1 nm).  
By approximation derived from second order polynomial.  
Dispersion slope = 0.074 ps/nm<sup>2</sup>/km.  
No external wavemeter was used, unless otherwise noted.
- \*10) Exchangeable by user.

Please be sure to read the product manual thoroughly before using the products.  
Specifications may change without notification.