



Agilent 909E

Precision Coaxial Termination

dc - 3 GHz, 75 Ω
Data Sheet



Features and description

Agilent's 909E is a precision, low reflection, 75 Ω load intended for use as a calibration standard.

Tantalum nitride on sapphire thin film technology is used for exceptional long-term impedance stability. To insure the best possible wear resistance characteristics, gold plated beryllium copper has been used for the connector contacts.

Specifications

Frequency range:

dc - 3 GHz (Option 909E-101 or Option 909E-011)

Impedance (nominal): 75 Ω

Connector:

909E and Option 909E-201 - type N (m)
Option 909E-011 - type N (f)

Reflection coefficient (max):

909E standard and Option 909E-011
dc - 2 GHz, 0.005 (1.01 SWR)
2 - 3 GHz, 0.01 (1.02 SWR)

Power rating: 500 mW average;
100 W peak, 10 μ S/pulse

Environmental

Temperature:

Operating: +15 to +35 $^{\circ}$ C
Non operating: -55 to +75 $^{\circ}$ C

Altitude:

Operating: 15,000 ft
Non operating: 50,000 ft

Humidity: Cycling five days,
+40 $^{\circ}$ C @ 95% RH

Vibration: 0.015", 5-55-5 Hz,
15 min., 3 axes

Shock: 200 g, 3 ms, three times each
plane

EMC: Radiation interference is within
the requirements of MIL-STD-461,
method RE02, VDE0871, CISPR
publication 11

Weight: net - 60 g (2 oz)
shipping - 200 g (8 oz)

Length: 51 mm (2 in)



Agilent Technologies

Agilent Technologies' Test and Measurement Support, Services, and Assistance

Agilent Technologies aims to maximize the value you receive, while minimizing your risk and problems. We strive to ensure that you get the test and measurement capabilities you paid for and obtain the support you need. Our extensive support resources and services can help you choose the right Agilent products for your applications and apply them successfully. Every instrument and system we sell has a global warranty. Support is available for at least five years beyond the production life of the product. Two concepts underlie Agilent's overall support policy: "Our Promise" and "Your Advantage."

Our Promise

Our Promise means your Agilent test and measurement equipment will meet its advertised performance and functionality. When you are choosing new equipment, we will help you with product information, including realistic performance specifications and practical recommendations from experienced test engineers. When you use Agilent equipment, we can verify that it works properly, help with product operation, and provide basic measurement assistance for the use of specified capabilities, at no extra cost upon request. Many self-help tools are available.

Your Advantage

Your Advantage means that Agilent offers a wide range of additional expert test and measurement services, which you can purchase according to your unique technical and business needs. Solve problems efficiently and gain a competitive edge by contracting with us for calibration, extra-cost upgrades, out-of-warranty repairs, and onsite education and training, as well as design, system integration, project management, and other professional engineering services. Experienced Agilent engineers and technicians worldwide can help you maximize your productivity, optimize the return on investment of your Agilent instruments and systems, and obtain dependable measurement accuracy for the life of those products.



Agilent Email Updates

www.agilent.com/find/emailupdates

Get the latest information on the products and applications you select.

Agilent T&M Software and Connectivity

Agilent's Test and Measurement software and connectivity products, solutions and developer network allows you to take time out of connecting your instruments to your computer with tools based on PC standards, so you can focus on your tasks, not on your connections. Visit

www.agilent.com/find/connectivity for more information.

By internet, phone, or fax, get assistance with all your test & measurement needs

Phone or Fax

United States:

(tel) 800 452 4844

Canada:

(tel) 877 894 4414

(fax) 905 282 6495

China:

(tel) 800 810 0189

(fax) 800 820 2816

Europe:

(tel) (31 20) 547 2323

(fax) (31 20) 547 2390

Japan:

(tel) (81) 426 56 7832

(fax) (81) 426 56 7840

Korea:

(tel) (82 2) 2004 5004

(fax) (82 2) 2004 5115

Latin America:

(tel) (305) 269 7500

(fax) (305) 269 7599

Taiwan:

(tel) 0800 047 866

(fax) 0800 286 331

Other Asia Pacific Countries:

(tel) (65) 6375 8100

(fax) (65) 6836 0252

Email: tm_asia@agilent.com

Online Assistance:

www.agilent.com/find/assist

Product specifications and descriptions in this document subject to change without notice.

© Agilent Technologies, Inc. 2002
Printed in USA, September 23, 2002
5952-0832



Agilent Technologies