# Dual Input Digital Thermometers

## **Temperature Meters**

Two fully functional, highly accurate meters offer dual K-type thermocouple inputs, RS-232 output port, and large LCD displays. Model 715 datalogging meter provides a triple LCD display that shows T1, T2 and T1-T2 simultaneously. The unit can log up to 16,000 datapoints with an adjustable interval. Model 710 offer a dual display where T1 and T2 can be switched between the large and small digits. While T1 - T2 is displayed on the large digits, T1 and T2 alternate on the small digits. With the optional ThermoLink software and RS-232 cable (AK-710), even Model 710 becomes a real-time datalogging meter when attached to a PC.

Both units offer:

- Max/Min ■ Data Hold
- Auto Power Off
- RS-232 output ports

### ■ °C/°F readings

- Model 715 Datalogging Temperature Meter
- Triple display
- Time reading

■ AC adapter port

## Model 710

**Temperature Meter** 

■ Datalogging RS-232 port

w/ cable and software

- Dual display
- RS-232 port
- △Rel Function
- Avg/Max/Min readings
  T1,T2 & T1-T2 select
- AC adapter port



Λ

228

715

710



#### Model 710 Dual-Display

	715	710
Measurement Range	-328°~2,498°F (-200°~1,370°C)	
Resolution	0.1°F (0.1°C)	
Accuracy	$\pm 0.2\%$ rdg $+2$ °F ( $\pm 0.2\%$ rdg $+1$ °C)	
Sensor Type	K-type thermocouple	
Input Protection	60V DC or 24V rms AC Maximum	
Sample Rate	I time per second	
Record (Datalogging)	16,000 Points	Does not apply
Datalogging Interval	00m:01s to 59m:59s	Does not apply
Operating Temp. & Humidity	32°~122°F (0°~50°C) & 10~80% RH	
Storage Temp	-4°~140°F (-20°~60°C)	
Power Supply	9V NEDA 1604 Battery (Optional Adapter BE-9)	
Battery Life	Approximately 100 hrs (Alkaline)	
Dimensions (LxWxH)	7.24 x 2.52 x 1.18" (184 x 64 x 30mm)	
Weight	11.3 oz. (320g)	1.66 lbs. (760g)

### Accessories

SUPPLIED: Instruction manual, Battery, 2 Bead Probes and Large carry case, Battery, 2 Bead Probes and Small carry pouch. OPTIONAL: BE-9 AC Adapter, AK-710 Thermolink Software w/RS-232 Cable (Model 710) See page 87 for K-type Thermocouple Probes

# www.valuetronics.com