

Features Include

- Analog Programmable
- Pulse Loading
- Variable Pulse Rate
- Variable Pulse Width
- Low Current Full Scale
- Fast Response Time
- Steady State Loading
- Economical & Compact

The DL Series of Dynaloads provides exceptional performance at an economical price. The series ranges from 100W modular loads to high current 3000W loads. Each unit has unique capabilities. Our DLVP series is ideal for the engineer who requires pulse load capability with the ability to change the duty cycle. The DLM series is designed for multi-channel DC sources and is rated at 100W per module. Four of the DLM modules can be installed in a 19" rack housing.





3000 Watt

DLVP 3000 Watt



- Pulse Loading
- Variable Pulse Rate
- Variable Pulse Width
- Analog Programmable

DLVP 50-300-3000B

OPERATION

Operating Voltage: 3 - 50 Volts **Operating Current:** 0 - 300 Amps **Power Dissipation:** 0 - 3000 Watts **Voltmeter Ranges:** 0 - 6 Volts 0 - 18 Volts

0 - 60 Volts

Ammeter Ranges: 0 - 36 Amps

0 - 120 Amps 0 - 360 Amps

Constant Current: 0 - 60 Amps

0 - 300 Amps

Constant Resistance: 0 - 20A/V

0 - 60A/V **Constant Voltage:** 0 - 50 Volts

Over Voltage: 60 Volts Max **Over Current:** 320 Amps Max **Power Limit:** 3400 Watts Frequency Range: 20Hz to 5KHz

Pulse Width: 10 - 100% Duty Cycle

Response Time: <50µS

Ext. Prog: to full scale current.

0 to 10 Volts input yields 0

±1% of setpoint from 10 to Prog. Accuracy:

100% of rated current

0-10 Volts for 0 to 100% of Current Sample:

Rated Current

<±3% Meter Accuracy: **MECHANICAL**

Size: 19"W x 8.75"H x 19.18"D

483mm W x 222mm H x 487mm D

19" Rack Mountable

42 lbs. / 19.05kg Weight: