



EasyView[™] Light Meters



Choice of models for high intensity measurements Up to 400,000 Lux and 40,000 Foot candles


Features:

- · Compact and rugged design features large display
- Multiple wide measuring ranges: Model EA30 - 40,000Fc in 4 ranges and 400,000Lux in 5 ranges Model EA31 - 20,000Fc in 4 ranges and 20,000Lux in 4 ranges
- · Data hold freezes reading on display
- MIN/MAX readings
- Cosine and color corrected measurements
- Low battery and overrange indication
- Auto power off to save battery life
- Utilizes precision silicon photodiode sensor with 3ft coiled cable for easy storage
- Complete with built-in stand, remote sensor with protective cover, protective rubber holster, and 6 AAA batteries

Additional features for Model EA30:

- Large display with bargraph
- Peak hold captures short light pulses to 100µSec
- · Relative function for zero or difference from reference value





High resolution for low level measurements in places like parking lots, stairwells, and ATM machines

Ordering Information:

EA30EasyView [™] High Intensity Light Meter			
EA30-NIST	EA30 with Calibration Traceable to NIST		
EA31EasyView [™] Light Meter			
EA31-NIST	EA31 with Calibration Traceable to NIST		

Specifications		Range	Resolution	Basic Accuracy
EA30	Lux	40, 400, 4000, 40000, 400000Lux	0.01	±3%rdg + 0.5%FS
	Foot candles	40, 400, 4000, 40000Fc		
EA31	Lux	20, 200, 2000, 20000Lux	0.01	±3%rdg + 0.5%FS
	Foot candles	20, 200, 2000, 20000Fc		
Dimensions		5.9 x 2.8 x 1.4" (150 x 72 x 33mm)		
Weight		8.3oz (235g)		

