

## 717 30G and 100G Pressure Calibrators

Compact, lightweight, and easy to carry



### 717 30G and 100G Pressure Calibrators

- Measure pressure, 0.05% of full scale with internal 30 or 100 psig sensor
  - 1/8 NPT pressure fitting
  - Compatible with non-corrosive gases and liquids
- Measure pressure to 10,000 psi/69 mPa using one of 29 Fluke 700Pxx Pressure Modules
- Measure mA with 0.025% accuracy and 0.001 mA resolution, while sourcing 24 V loop power
- Calibrate P/I or I/P transmitter with simultaneous pressure and current measurement
- Select from eleven different engineering units
- Zero, min, max, and hold functions

### General features

- Compact and lightweight
- Simple controls
- Clear, 5-digit, liquid crystal display
- Operating temperature: -10 °C to 55 °C
- Safety: CSA C22.2 No. 1010.1:1992
- Three-year warranty
- Included:
  - Fluke 717 30G or 100G Pressure Calibrator
  - Protective yellow holster with Flex-Stand™
  - Test leads and alligator clips
  - Single 9 V alkaline battery
  - Instructions (14 languages)

### General specifications

**Maximum voltage:** 30 volts  
**Non-operating temperature:** -40 °C to 60 °C  
**Operating temperature:** -10 °C to 55 °C  
**Relative humidity:** 95% (10 °C to 30 °C); 75% (30 °C to 40 °C); 45% (40 °C to 50 °C); 35% (50 °C to 55 °C)  
**Operating altitude:** 3,000 m max  
**Shock:** 1 m drop test  
**Vibration:** Random, 2 g, 5-500 Hz  
**Safety:** CSA C22.2 No. 1010.1:1992  
**EMC:** EN50082-1:1992 and EN55022:1994 Class B  
**Size/weight:** 187 mm L x 87 mm W x 32 mm D (7.35 in L x 3.41 in W x 1.25 in D) 330 g (12 oz)  
**Size/weight (with holster and FlexStand™):** 201 mm L x 98 mm W x 52 mm D (7.93 in L x 3.86 in W x 2.06 in D) 600 g (21 oz)  
**Power:** 9 V battery ANSI/NEDA 1604A or IEC 6LR619V alkaline  
**Battery life:** 4 to 20 hours, typical, depending on functions used  
**Warranty:** Three years

**Fluke.** Keeping your world up and running.

### Specifications (18 °C to 28 °C, one year)

	Function	Range	Resolution	Accuracy	Notes
717 100G	Measure pressure <sup>1</sup> (internal sensor) Over pressure 3xFS	-12 - 100 psi (-83 - 690 kPa)	0.01 psi (10.1 kPa)	0.05 % FS	Gases/liquids (non-corrosive) zero, min, max, hold, damp
717 30G	Measure pressure <sup>1</sup> (internal sensor) Over pressure 3xFS	-12 - 30 psi (-83 - 207 kPa)	0.001 psi (0.01 kPa)	0.05 % FS	Gasses/liquids (non-corrosive) zero, min, max, hold, damp
	Measure pressure <sup>1</sup> (with pressure modules) over pressure per pressure module specs	29 pressure modules, 10 in. H <sub>2</sub> O/ 2.5 kPa to	To 0.0001 psi, per pressure module specs <sup>2</sup>	To .025 % of full span, per pressure module specs <sup>2</sup>	Media compatibility per pressure module specs <sup>2</sup> zero, min, max, hold, damp
	Measure mA	0 to 24 mA	0.001 mA	0.025 % + 1 count	
	Loop supply	24 V dc	N/A	± 10 %	Drive; 20 mA into 1000 Ω for battery >6.8 V; 700 Ω for battery 5.8 to 6.8 V

<sup>1</sup>Supported pressure units; psi, in. H<sub>2</sub>O (4 °C), in. H<sub>2</sub>O (20 °C), cm H<sub>2</sub>O (4 °C), cm H<sub>2</sub>O (20 °C), bar, mbar, kPa, inHg, mmHg, kg/cm<sup>2</sup>  
<sup>2</sup>See pressure module specs, per lit code 1281620

### Ordering Information

Fluke-717 30G Pressure Calibrator  
 Fluke-717 100G Pressure Calibrator

Need technical assistance? Call:

**1-800-44-FLUKE**

Toll-free in the U.S.

(905) 890-7600 in Canada

+1 (425) 446-5500 other countries

For more information to be sent to you by fax, call 1-800-FLUKE-FAX in the U.S. and Canada. Or, visit our website at [www.fluke.com](http://www.fluke.com)