



**Immense technology. In the palm of your hand.**

THT45|46 are ultra compact cameras with an incredibly light weight.



**Not just infrared.**

Thanks to new technology PiP you can mix thermal and visual image.

## Tech specs

### › IMAGING PERFORMANCE

#### Thermal

Detector type	UFPA
Spectral range	8 ÷ 14µm
Resolution / Pxl size	<b>THT45</b> 80x80pxl/34µm <b>THT46</b> 160x120pxl/25µm
Thermal sensitivity	<0.1 °C @ 30°C
Field of view (FOV)	<b>THT45</b> 17°x17° (9mm Lens) <b>THT46</b> 25°x19° (9mm Lens)
Minimum focal distance	0.5m
IFOV (@1m)	<b>THT45</b> 3.78mrad <b>THT46</b> 2.78mrad
Focusing	Manual
Image frequency	50Hz
Color palettes	4 (Iron, Rainbow, Grey, Inverse Grey)

#### Visible

Integrated camera	1.3Mpxl, FOV 59°
-------------------	------------------

### › IMAGING / IR VIDEO DISPLAY

Display type	2.8" color LCD, 320x240pxl
Infrared PiP Fusion	IR image inside visible & visible image inside IR
IR / Video	Recording and saving on Micro SD card MPEG4 file format
Video output	HDMI
Electronic zoom	x1 ÷ x32

### › MEASUREMENT

Temperature range	-20°C ÷ 350°C
Measurement unit	°C, °F, °K
Accuracy	±2 % reading or ±2°C
Measurement cursors	3 (MIN, MAX, FIXED)
Laser pointer	Class 2 according to IEC 60825-1
Built-in illuminator	White light LED
Measurement modes	Automatic / Manual
Emissivity correction	0.01 ÷ 1.00 + built-in table with common materials
Measurements features	Automatic correction based on emissivity and offset

### › IMAGE STORAGE AND PC INTERFACE

Memory	Micro SD card 8GB
File format	JPEG standard
Memory size	> 2000 images
PC interface	USB 2.0 (for video and image transfer)

### › POWER SYSTEM

Battery type	Rechargeable Li-ION - 3,7V 2000mAh
Charging system	Built-in
Battery life	4 hours of continuous use
External power	External adapter 100/240VAC (50/60Hz)/12VDC

### › GENERAL SPECIFICATIONS

Operating temperatures	-20°C ÷ 50°C
Operating humidity	10% ÷ 90%HR
Storage temperature	-40°C ÷ 70°C
Storage humidity	10% ÷ 90%HR
Encapsulation	IP50 according to IEC529
Shock	25G, according to IEC60068-2-29
Vibrations	2G, according to IEC60068-2-6
Drop test	2m
Dimensions (L x W x H)	224 x 77 x 96mm
Weight (battery included)	0.5kg

LOCAL REPRESENTATIVE

# THT45|46 ESPRESSO SIZE INFRARED CAMERAS



**HT ITALIA S.R.L.**  
Via della Boaria, 40  
48018 Faenza (RA) Italia  
T +39 0546 621002  
F +39 0546 621144  
E-mail export@htitalia.it  
ht-instruments.com

**HT INSTRUMENTS AMERICAS LLC**  
3145 Bordentown Avenue  
W3, Parlin, NJ 08879  
USA  
Tel. 1 719 421 9323  
E-mail: sales@ht-instruments.us  
ht-instruments.us

**HT INSTRUMENTS GMBH**  
Am Waldfriedhof, 1b  
D-41352 Korschenbroich, Deutschland  
Tel. + 49 (0)2161 564 581  
Fax + 49 (0)2161 564 583  
E-mail: info@ht-instruments.de  
ht-instruments.de

**HT INSTRUMENTS SA**  
C/ Legalitat, 89  
08024 Barcelona, España  
Tel. +34 93 4081777  
Fax +34 93 4083630  
E-mail: info@htinstruments.es  
ht-instruments.es



# THT45|46 COMPACT INFRARED CAMERAS



## A very gifted series.

- › LED Flash
- › Visual image camera
- › Laser pointer



## Stay connected.

- › USB 2.0 PC connection
- › Video HDMI output
- › MicroSD data saving
- › Mini USB Plug for recharge/power supply



## All answers. In one software.

- › Innovative display
- › **New** drop down menu
- › **Simple** and smart interface
- › **Fast access** to all commands
- › Fixed cursor + **2 mobile cursors** for **MIN** and **MAX** temperature
- › **P.i.P.** Visible spectrum and **thermal imaging overlap**
- › **Video IR** recording
- › Thermal sensitivity **0,1°C**
- › Temperature range **-20/+350°C**
- › **Automatic SPAN** adjustment
- › Selection of material to be inspected to **set automatic emissivity**
- › Ready to use **pre-set table of material**



160x120  
80x80\*  
pixel  50 hz

## Best display ever.

- › **2,8"** extra bright, wide display
- › Superior **sharpness** and image quality
- › **Oversampling** technology
- › **50Hz** refresh frequency

\* THT45.



## Unstoppables. Unbreakables.

- › 3,7V 2600mA Li-ION **rechargeable battery**
- › Up to **4 and a half hours** of continuous use
- › **Built-in charger** and external adapter
- › **Soft carrying bag** to carry the camera and the accessories

## THTLink™. That's it.

- › **Innovative** PC Software
- › **Easy to use** interface
- › **Thorough analysis**
- › Picture **Adjustment**
- › Creation of **professional reports**

