

American Hakko Products, Inc.

PRODUCT BULLETIN

 Bulletin No:
 PB438

 Issue Date:
 7-9-2019

 Effective Date:
 7-30-2019

Description/Title:

New HAKKO FG-101B Soldering Iron Tester

Part No: FG101B-03



Specification:

Specification.				
Model No.		FG-101B		
Part No.		FG101B-03		
Temperature	Resolution	1°F	1°C	
	Range of Measurement ¹	32 – 1300°F	0 – 700°C	
	Applicable Sensor	K(CA) Type The	rmocouple	
	Measurement	±6°F	±3°C	
	Tolerance ²	(572 – 1112°F)	(300 – 600°C)	
Voltage	Resolution	0.1mV		
	Measurement range	0-40mV (AC)		
	Precision	± (5% + 1	digit)	
Resistance	Resolution	0.1 ohms		
	Measurement range	0-40 oh	ms	
	Precision	± (5% + 1	digit)	
Display	Liquid Crystal Display	3.5 digit		
	Burnout	-/		
	MAX HOLD	Refer to m	anual	
	AUTO HOLD	Refer to m	anual	
	Temperature	000 to 999	times	
	measurement count			
Power Consumption		120V/3.2W		
Dimensions (W x H x D)		211 x 53 x 126 mm		
(excluding protrusions)		(8.31 x 2.09 x 4.96 in)		
Weight		0.95kg (2.09 lb.)		
Operating Environment		0-40°C (32-104°F)		
		Max 80% RH (without condensation)		
Pollution Degree Rating		Pollution Degree 2		
		1		

^{1 –} Temperature sensor (PN: 191-212) can only be used to measure temperatures below 500°C (932°F). To measure higher temperatures, use an applicable temperature probe.

² – Measurement tolerance is $\pm 5^{\circ}$ C / $\pm 10^{\circ}$ F for measurements outside the rage given for measurement tolerance above.



American Hakko Products, Inc.

Standards & Ratings	(MET). (E
---------------------	------------

Contents:

Part No.	Description	
	FG-101B Soldering Tester	
	User Manual	
191-212	Replacement Sensor (Pack of 10)	
B2468	Fuse / 125V-5A (Spare)	
B1950	Conductive Wire	
B1754	Grounding Clip	
B2419	Power Cord	

Comments:

The NEW Hakko FG-101B Soldering Iron Tester replaces the discontinued Hakko FG-101 and will be available July 30, 2019.

The FG-101B measures soldering iron tip temperatures, leak voltage and tip-to-ground resistance, as well as solder pot temperatures (with optional temperature probe). It includes all features from the FG-101 such as the MAX HOLD and AUTO ZERO. In addition, the FG-101B now includes a new AUTO HOLD feature. With this function the measurements will end automatically once the measurement is stabilized, which can minimize individual differences in measurements. The FG-101B also has a user selectable temperature display which allows the reading to display in either °C or °F and a measurement counter that helps to monitor your temperature sensor usage.

AUTO HOLD and MAX HOLD cannot be used simultaneously.

For more information, please visit www.HakkoUSA.com, e-mail Support@HakkoUSA.com, or call 1-800-88-HAKKO (42556).