

Soldering Iron

Station Type Heavy Duty Soldering Iron

SOLDERING STATION FX-801

Go Beyond the Limits! Super Power 300W to Change the World of Soldering



Make the impossible possible with Super Power of 300W Heaters.

FX-801 can provide tremendous heating performance with super power 300W composite tip.

workability.

Handles on unit body

Handles on unit body make it easy to carry after work.

Easy tip replacement makes tip replacement easy.

Sleep/Shut-off function

Safety design automatically enters sleep/shut-off function when iron is placed in iron holder. The function automatically cools down tip temperature and shut-off power when not in use for a certain period of time.

An LED display roughly double the size of a conventional model is very easy to see. **Password function**

HAKKO FX-801 時早

Settings can be locked from unnecessary changes by password function.



Large LED display

www.valuetronics.com

Preset mode

Up to 6 settings can be preset and easily called up by Up/Down buttons.



Compact and lightweight (50g) for heavy duty 300W iron


The same weight as the FM-2030 handpiece for comfort and better

The composite tip, a tip integrated heating element,

Compatible with N2 System


Replacing an iron part (FX-8002) with an optional N2 iron part (FX-8003), enables use of N2 system.

Appropriate option nozzles for each tip shape are necessary.



FX-801

Packing List



HAKKO FX-801 Heavy Duty Soldering Iron

Soldering station (HAKKO FX-801), Soldering iron (FX-8002), Heat resistant pad, Power cord, Connecting cable, Iron holder (with cleaning sponge and cleaning wire), Instruction manual

Specifications

Weight (without cord)

Station Power consumption 300W Output voltage AC 29V Temperature range 50 to 500 Temperature stability ±5 at idle temperature Dimensions 145(W)×107(H)×211(D) mm 3.9 kg Weight Soldering Iron Power consumption 260W (29V) Tip to ground resistance < 2 Tip to ground potential < 2 mVCord length 1.2 m Total length (without cord) 228 mm (with T33-BC4)

50 g (with T33-BC4)

HAKKO CORPORATION

OVERSEAS AFFILIATES

HEAD OFFICE

4-5, SHIOKUSA 2-CHOME, NANIWA-KU, OSAKA, 556-0024 JAPAN TEL:+81-6-6561-3225 FAX:+81-6-6561-8466 http://www.hakko.com E-mail:sales@hakko.com

U.S.A. AMERICAN HAKKO PRODUCTS, INC.

28920 AVENUE WILLIAMS VALENCIA, CA 91355, U.S.A. TEL: (661) 294-0090 FAX: (661) 294-0096 Toll Free (800)88-HAKKO (42556)

http://www.hakkousa.com WWWpercallelaOujetCS.COM Copyright Hakko Corporation. All right reserved. CA00461GbYa001 2015.1