

# Split-box Pipe and Cable Locator



- Energized or de-energized lines tracing
- Conductive or inductive coupling
- Peak and null detection capabilities
- Hand-held and lightweight
- Solid construction in a tough, plastic housing

## DESCRIPTION

The Split-box Pipe and Cable Locator is a hand-held instrument in the classic “split-box” design, consisting of a transmitter and a receiver. The instrument traces underground conductive networks such as water and gas mains, telephone, cable TV, and electric power cables. It determines buried lines depth and locates underground metallic masses such as valve caps and manhole covers.

Designed with patented super-inductive technology, the Split-box Pipe and Cable Locator is lightweight, portable, and easy to use. For easy transport, the instrument and accessories are supplied with a protective tote bag.

## APPLICATIONS

To locate and trace an underground metallic line, the line is energized with a radio-frequency signal generated by the transmitter and then detected by the receiver. Inductive or conductive modes of operation are available.

The inductive operational mode does not require direct mechanical line connection. The transmitter can energize a buried line without the need to uncover it. Just place the transmitter on the ground or pavement above the line which, once induced with the transmitted signal, retransmits the signal through the ground and air in a pattern that corresponds to its path. The line carries the signal several hundred yards depending on its depth, the mineralization and conductivity of the soil, and the transmitter power setting.

The conductive mode of operation requires the line to be exposed so that a direct connection can be made. Conductive energizing is preferred over inductive energizing because it results in more highly defined signal coupling. The signal generated does not spread to other conductive lines in the vicinity of the traced line. Using a ground rod with the direct connection increases the energizing efficiency and, therefore, the length of line that can be traced.

Two methods of receiving the transmitted signal are peak detection and null detection. The method used depends on the placement of the receiver. When held at a right angle to the surface of the ground and moved back and forth across the line to be traced, the receiver detects peaks (maximum signals) when directly above the line. When the receiver is held so its face is parallel to the surface of the ground and moved back and forth across the line, the detection of minimum signal or null (absence of signal) indicates that the line is directly below.

## FEATURES AND BENEFITS

- **Lightweight and portable** — half the physical size of Standard Split-Box Pipe and Cable Locator
- **Virtually Indestructible** — long lasting and can withstand tough field environments
- **Built-in mass locator** — same Instrument can locate cables, pipes, manhole covers, and valve caps

**SPECIFICATIONS**

**Output Frequency**

126 kHz

**Batteries**

4 each "C" Size Alkaline Batteries for transmitter and receiver

**Battery Life**

50 Hours

**Audio Output**

Built-In speaker and headphone jack

**Sensitivity**

Manual Signal Adjust

**Operating Temperature**

-5° F to 158° F (-20° C to 70° C)

**Dimensions**

**Transmitter**

6.5 H x 2.375 W x 8.5 D in.  
(165 H x 60 W x 215 D mm)

**Receiver**

6.5 H x 2.375 W x 8.5 D in.  
(165 H x 60 W x 215 D mm)

**Weight**

**Transmitter:** 2.5 lb (1.1 kg)

**Receiver:** 2.5 lb (1.1 kg)

**ORDERING INFORMATION**

<b>Item (Qty)</b>	<b>Cat. No.</b>
Split-box Pipe and Cable Locator	656902
<b>Included Accessories</b>	
Batteries (4 ea.)	19111
Protective tote bag	656920-1
Direct connection cable, 3 ft	656920-2
Ground rod	656920-3
Instruction manual	AVTM656902
<b>Optional Accessories</b>	
Induction clamp	656626
Mini Headset	656920-4
Large carrying case (holds Induction clamp and larger direct connection cable)	656920-5
Direct connection cable, 6 ft.	656920-6
Receiver carrying strap	656920-7

**UK**  
Archcliffe Road, Dover  
CT17 9EN England  
T (0) 1 304 502101  
F (0) 1 304 207342

**UNITED STATES**  
4271 Bronze Way  
Dallas, TX 75237-1018 USA  
T 1 800 723 2861  
T 1 214 333 3201  
F 1 214 331 7399

**OTHER TECHNICAL SALES OFFICES**  
Norristown USA, Toronto CANADA,  
Mumbai INDIA,  
Le Raincy FRANCE, Cherrybrook  
AUSTRALIA, Guadalajara SPAIN  
and The Kingdom of BAHRAIN.

**ISO STATEMENT**  
Registered to ISO 9001:1994 Reg no. Q 09250  
Registered to ISO 14001 Reg no. EMS 61597  
**SPLITBOX\_DS\_en\_V01**  
[www.megger.com](http://www.megger.com)  
Megger is a registered trademark