

Protek A734

4.4GHz Handheld Spectrum Analyzer

Protek is ready to provide you with good solution and good service that you need anytime and anywhere.

- ▶ The Economical Solution
- ▶ Ideal for Field Testing
- ▶ Lightweight and Easy-to-use



Protek A734 4.4GHz Handheld Spectrum Analyzer



Protek A734 4.4GHz Handheld Spectrum Analyzer



▶ Side



Interface (USB, LAN)

▶ Front





Keypad with Knob

▶ Bottom



Smart Battery (8 hours)





A734 is Hand-Held type spectrum analyzer with a frequency range of 100 kHz to 4.4 GHz .

This equipment is suitable for signal analysis which can be used as frequency , digital information are more important these days.

A734 Hand-Held Spectrum Analyzer has been designed for use in the process of development, adjustment and testing of various electronic devices in industrial and laboratory facilities, including operation as a component of an automated measurement system. .

The equipment provide a variety of functions and user-friendly interface so user can operate for management and test about frequency and amplitude.



Protek A734 4.4GHz Handheld Spectrum Analyzer

Specifications

Item		Specification		
Frequency	Range	100 kHz to 4.4GHz		
	Span Mode	Center Freq + Span or Start Freq + Stop Freq ,ZERO Span		
	Span	ZERO SPAN , 600 Hz to 4.4GHz		
	Minimum Span	600 Hz		
	Internal Frequency Reference Accuracy	± 1PPM		
	Frequency Readout Accuracy	Reference error ± 1 sample		
	Marker Accuracy	Reference error ± 1 sample		
Amplitude	Measurement Range	DANL – 1dB Gain Compression		
		1dB Gain Compression(attenuator 15dB, preamp off)		
		+16dBm Typical, 1Hz to 150MHz		
		+19dBm Typical, 150MHz to 4.4GHz		
	DANL	Displayed Average Noise Level : 0dB ATT, 1Hz RBW		
		FREQ	Preamp OFF	Preamp ON
		10Hz	-124dBm	NA
		100Hz to 10kHz	-130dBm	NA
		10kHz to 500kHz	-142dBm	NA
		500kHz to 10MHz	-142dBm	-153dBm
		10MHz to 100MHz	-148dBm	-161dBm
		100MHz to 1GHz	-144dBm	-158dBm
		1GHz to 2.6GHz	-139dBm	-151dBm
	2.6GHz to 3.3GHz	-135dBm	-151dBm	
	3.3GHz to 4.4GHz	-128dBm	-134dBm	
	Amplitude unit	dBm, Watt		
	Absolute Accuracy (ref level < 0dBm)	± 1.5dB Typical		
Absolute Accuracy (0dBm< ref level < 10dBm)	± 1.5dB			
Relative Accuracy (ref level < 0dBm)	± 0.25			
Maximun Safe Input Level (preamp off, 15dB att)	+20dBm			
DC Volt	±0.2V max			
Sweep	Zero Span Sweep Time	10 ms to 2 sec (±0.1%) All other sweep times are estimates reported after sweep completes		
	Sweep Triger	freerun, single, external		
	External Trigger	3.3V CMOS/TTL input		
Display	TRACE	3 Trace		
	DETECTOR	min, max, sample , avg (power , voltage , log)		
	Marker	5 Marker		
	Marker function	peak, next peak, center=marker frequency,		
	Audio Demodulation	AM & FM		
	Type	5.7" Color TFT-LCD 640*480 pixels		
	Display Resolution	640*480 pixels		
	Feature	SunLight Readable		
Input	KeyPad Back Light	ON/OFF		
	RF Connector	RF Signal IN, N type Female 50OHM		
	BNC External Timebase	10MHz in, BNC type Female		
General Spec	BNC Share	Self test, Sync out, Sweep Trigger IN, BNC type Female		
	Operating Environment	-10°C to +50°C < 95%		
	Humidity	< 95%		
	Storage Temperature	-20°C to +60°C		
Power	Battery	Li-ion Rechargeable Battery 6Cell(normal 7.4V / 7800mA)		
	Power Adaptor	AC Input	AC 100-240 V- ,50/60 Hz, 1.5A	
		DC Output	DC 12Vd.c. / 5.0A	
Dimension	Size	160(W) X 263(H) X 61(D) mm		
Weight		1.75 Kg (include battery)		
Other	Speaker	0.5W 8ohm Speaker 1Ch		
	AF out			
	Interface	Storage (USB port), LAN (RJ-45 Port)		
Environmental		For Indoor use		
		Altitude up to 2000m		
		Pollution Degree 2°		

Protek
It measures even what you think!

This is global
GSI

HEAD OFFICE

GS Instruments Co.,Ltd.

70, Gilpa-ro 71beon-gil, Nam-gu, Incheon 402-854, Korea
Tel : +82-1688-6820
Fax : +82-32-870-5640
isale@gsinstrument.com
www.gsinstrument.com

USA OFFICE

GS Teletech Inc.

320 NW Victoria Dr, Lee's Summit MO64086, USA
Tel : +1-913-469-6699
Fax : +1-913-661-0163
protek@gsteletechinc.com
www.gsteletechinc.com

www.gsi-protek.com

www.valuetronics.com