

Tektronix Logic Analyzers

TLA7N4 Logic Analyzer Module Data Sheet



Features & Benefits

- 136 Channel Logic Analyzer with up to 8 Mb Depth
- MagniVu™ Acquisition Technology Provides 2 GHz (500 ps) Timing Resolution to Find Difficult Problems Quickly
- Up to 200 MHz State Acquisition Analysis of Synchronous Digital Circuits
- Simultaneous State and High-speed Timing Analysis through the Same Probe Pinpoints Elusive Faults without Double Probing
- 500 MHz Deep Timing Analysis with up to 8 Mb Per Channel
- Glitch and Setup/Hold Triggering and Display Finds and Displays Elusive Hardware Problems
- Transitional Storage Extends the Signal Analysis Capture Time
- Broad Processor and Bus Support
- Full Range of General-purpose and High-density, Nonintrusive Probes

Applications

- Hardware Debug and Verification
- Processor/Bus Debug and Verification
- Embedded Software Integration, Debug, and Verification

Breakthrough Solutions for Real-time Digital Systems Analysis

Today's digital design engineers face daily pressures to speed new products to the marketplace. The TLA7N4 logic analyzer module answers the need with breakthrough solutions for the entire design team, providing the ability to quickly monitor, capture and analyze real-time digital system operation in order to debug, verify, optimize, and validate digital systems.

Hardware developers, hardware/software integrators, and embedded software developers will appreciate the range of capabilities of the TLA7N4 logic analyzer module. Its broad feature set includes capturing and correlating elusive hardware and software faults; providing simultaneous state and high-speed timing analysis through the same probe; using deep state acquisition to find the cause of complex problems; real-time, nonintrusive software execution tracing that correlates to source code and to hardware events; and nonintrusive probing.

The TLA7N4 logic analyzer module offers Tektronix' breakthrough MagniVu™ technology for providing high-speed sampling (up to 2 GHz) that dramatically changes the way logic analyzers work and enables them to provide startling new measurement capabilities.

The TLA7N4 module offers high-speed state synchronous capture and high-speed timing capture through the same set of probes. It capitalizes on MagniVu technology to offer 500 ps timing on all channels, glitch and setup/hold triggering and display, and time stamp that is always on at up to 500 ps resolution.

The TLA7000 Series logic analyzer modules are ideal for timing analysis, multiprocessor/bus applications, and embedded software analysis.

Characteristics

General

Number of Channels (all channels are acquired including clocks) – TLA7N4: 136 channels (4 are clock and 4 are qualifier channels).

Channel Grouping – No limit to number of groups or number of channels per group (all channels can be reused in multiple groups).

Module "Merging" – Three modules can be "merged" to make up to a 408-channel module. Merged modules exhibit the same depth as the lesser of the three individual modules. Word/range/setup-and-hold/glitch/transition recognizers span all three modules. Only one set of clock connections is required.

Time Stamp – 50 bit at 500 ps resolution (6.5 day range).

Clocking/Acquisition Modes – Internal, internal 2x, external. 2 GHz MagniVu high-speed timing is available simultaneous with all modes.

Number of Mainframe Slots Required per TLA Series Module – 2

Input Characteristics

(with P6417, P6418, P6419, or P6434 probes)

Capacitive Loading – <0.7 pF data and clock (P6419).

1.4 pF typical data; 2 pF typical clock (P6418).

2 pF typical data and clock (P6417 and P6434).

Threshold Selection Range – From +5.0 V to -2.0 V in 50 mV increments.

Threshold Selection Channel Granularity – Separate selection for clock (1) and data (16) for each 17-channel probe connector.

Threshold Accuracy (including probe) – ± 100 mV.

Input Voltage Range –

Operating: $6.5 V_{pp}$ centered around the programmed threshold.

Nondestructive: ± 15 V.

Minimum Input Signal Swing – 250 mV or 25% of signal swing, whichever is greater (P6417, P6418, and P6419).

300 mV or 25% of signal swing (P6434).

Input Signal Minimum Slew Rate – 200 mV/ns typical.

State Acquisition Characteristics

(with P6417, P6418, P6419, or P6434 probes)

State Clock Rate – 100 MHz standard, 200 MHz optional.

State Data Rate (half/full channels) – 400/200 Mb/s, typical. Requires 200 MHz state option.

State Memory Depth with Time Stamps – 64 Kb, 256 Kb, 1 Mb, or 4 Mb per channel.

Setup-and-Hold Time Selection Range – From 8.5 ns before, to 7.0 ns after clock edge.

Setup-and-Hold Window – 2 ns typical.

Minimum Clock Pulse Width – 2 ns.

Active Clock Edge Separation – 5 ns.

Demux Channel Selection – Channels can be demultiplexed to other channels through user interface with 8-channel granularity.

Timing Acquisition Characteristics

(with P6417, P6418, P6419, or P6434 probes)

MagniVu™ Timing – 500 ps.

MagniVu Timing Memory Depth – 2 Kb (2048) per channel.

Deep Timing Resolution (half/full channels) – 2/4 ns to 50 ms.

Deep Timing Resolution with Glitch Storage Enabled – 10 ns to 50 ms.

Deep Timing Memory Depth (half/full channels with time stamps and with or without transitional storage) – 128/64 Kb, 512/256 Kb, 2/1 Mb, 8/4 Mb per channel.

Deep Timing Memory Depth with Glitch Storage Enabled – Half of default main memory depth.

Channel-to-Channel Skew – <1 ns typical.

Minimum Recognizable Pulse Width (single channel) – 2 ns.

Minimum Recognizable Glitch Width (single channel) – 2 ns.

Minimum Recognizable Multichannel Trigger Event – Sample period +2 ns.

Trigger Characteristics

Independent Trigger States – 16

Maximum Independent If/then Clauses per State – 16

Maximum Number of Events per If/then Clause – 8

Maximum Number of Actions per If/then Clause – 8

Maximum Number of Trigger Events – 18 (2 counters/timers plus any 16 other resources).

Number of Word Recognizers – 16

Number of Range Recognizers – 4

Number of Transition Recognizers – 1

Number of Counters/Timers – 2

Trigger Event Types – Word, group, channel, transition, range, anything, counter value, timer value, signal, glitch, setup-and-hold violation.

Trigger Action Types – Trigger module, trigger all, store, don't store, start store, stop store, increment counter, reset counter, start timer, stop timer, reset timer, goto state, set/clear signal, do nothing.

Trigger Sequence Rate – DC to 250 MHz (4 ns).

Counter/Timer Range – 51 bits each (>100 days at 4 ns).

Counter Rate – DC to 250 MHz (4 ns).

Timer Clock Rate – 250 MHz (4 ns).

Counter/Timer Latency – None (can be tested or reset immediately after starting).

Range Recognizers – Double bounded (can be as wide as any group, must be grouped according to specified order of significance).

Setup-and-Hold Violation Recognizer Setup Time Range – From 8 ns before to 7 ns after clock edge in 0.5 ns increments.

Setup-and-Hold Violation Recognizer Hold Time Range – From 7 ns before to 8 ns after clock edge in 0.5 ns increments.

Trigger Position – Any data sample.

MagniVu Trigger Position – MagniVu data is centered around the module trigger.

Storage Control (data qualification) – Global (conditional), by state (start/stop), by trigger action, or transitional.

Storage Window Granularity – Single sample or block-of-31 samples before and after.

Safety – CSA C22.2 No. 1010.1, EN61010-1, IEC61010-1, UL 3111-1.

Physical Characteristics

Dimensions	mm	in.
Height	262	10.3
Width	61	2.4
Depth	381	15
Weight	kg	lb.
Net (w/o probes)	3.1	6.7
Shipping (typical)	6.3	13.7

Ordering Information**TLA7N4 Logic Analyzer Module**

Includes: Probe retainer bracket, probe manual, certificate of calibration, one-year warranty (return to Tektronix), and user manual.

Probes must be ordered separately.

TLA7N4 – 136-channel Logic Analyzer module, 2 GHz timing, 100 MHz state, 64 Kb depth. Options for up to 4 Mb depth and/or 200 MHz state.

Logic Analyzer Module Options

(Base configuration is 64 K depth at 100 MHz state)

Opt. 1S – Increase to 256 K depth at 100 MHz state.

Opt. 2S – Increase to 1 M depth at 100 MHz state.

Opt. 3S – Increase to 4 M depth at 100 MHz state.

Opt. 4S – Increase to 64 K depth at 200 MHz state.

Opt. 5S – Increase to 256 K depth at 200 MHz state.

Opt. 6S – Increase to 1 M depth at 200 MHz state.

Opt. 7S – Increase to 4 M depth at 200 MHz state.

TLA7N4 Service Manual and Test Fixtures

TLA7N4 Logic Analyzer Performance Verification and Adjustment Fixture (includes AC adapter; requires local power cord) – Order 671-3599-xx

TLA7N4 Logic Analyzer Modules Service Manual (includes Performance Verification and Adjustment procedures) – Order 071-0864-xx

TLA Series Module Upgrades

You can increase the memory depth and state speed of most existing TLA Series logic analyzer modules. You can also install a TLA7N4 logic analyzer module into an existing TLA715/721/7XM/7012/7016 mainframe. Please refer to the TLA Family Upgrade Guide for further details.

Logic Analyzer Probe Selection Guidelines

There are a number of flexible choices of logic analyzer probes available for use with TLA Series logic analyzer modules. Please see logic analyzer probe data sheets for more information.

Logic Analyzer Module Probes and Accessories**TLA7N4 Service Options**

Opt. C3 – Calibration Service 3 Years

Opt. C5 – Calibration Service 5 Years

Opt. D1 – Calibration Data Report

Opt. D3 – Calibration Data Report 3 Years (with Opt. C3)

Opt. D5 – Calibration Data Report 5 Years (with Opt. C5)

Opt. R3 – Repair Service 3 Years

Opt. R5 – Repair Service 5 Years

Opt. IN – Product Installation Service



Product(s) are manufactured in ISO registered facilities.

Contact Tektronix:

- ASEAN / Australasia** (65) 6356 3900
- Austria** +41 52 675 3777
- Balkans, Israel, South Africa and other ISE Countries** +41 52 675 3777
- Belgium** 07 81 60166
- Brazil** +55 (11) 3759-7627
- Canada** 1 (800) 661-5625
- Central East Europe, Ukraine, and the Baltics** +41 52 675 3777
- Central Europe & Greece** +41 52 675 3777
- Denmark** +45 80 88 1401
- Finland** +41 52 675 3777
- France** +33 (0) 1 69 86 81 81
- Germany** +49 (221) 94 77 400
- Hong Kong** (852) 2585-6688
- India** (91) 80-42922600
- Italy** +39 (02) 25086 1
- Japan** 81 (3) 6714-3010
- Luxembourg** +44 (0) 1344 392400
- Mexico, Central/South America & Caribbean** 52 (55) 54247900
- Middle East, Asia, and North Africa** +41 52 675 3777
- The Netherlands** 090 02 021797
- Norway** 800 16098
- People's Republic of China** 86 (10) 6235 1230
- Poland** +41 52 675 3777
- Portugal** 80 08 12370
- Republic of Korea** 82 (2) 6917-5000
- Russia & CIS** +7 (495) 7484900
- South Africa** +27 11 206 8360
- Spain** (+34) 901 988 054
- Sweden** 020 08 80371
- Switzerland** +41 52 675 3777
- Taiwan** 886 (2) 2722-9622
- United Kingdom & Ireland** +44 (0) 1344 392400
- USA** 1 (800) 426-2200

For other areas contact Tektronix, Inc at: 1 (503) 627-7111

Updated 5 August 2009

For Further Information. Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit www.tektronix.com



Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

17 Aug 2009

52W-18099-2

www.tektronix.com

