

MG-High airflow systems

Filtronic Sweden	Article number	Description
	100-1000-ESD	Filter unit MG100S Filter unit operated by electricity for fumes and gases for connection to two extraction arms.
		Technical data MG100SHeight (mm)610Width (mm)460Depth (mm)210Weight incl filter cartridge (kg)21Noise level dB(A) 1 m52Voltage 1-phase 50/60Hz (Volt)100-240Effect (Watt)100Max. suction capacity (m³/hr)100Micro filter HEPA -styled - separation degree DOP>99,97%Gas filter - Chemisorbtion media, efficiency>93%Eiben separation degree Dope>93%
	100-1032-ESD	Filter alarm Yes, light/sound
		2 pcs of extraction arm 4002 are included in the delivery.
	100-1055-ESD	Filter Unit MG100S with flexible extraction arms Ø 55 mm 2 pcs of extraction arm 3035 are included in the delivery.
	100-2000-ESD 100-2003-ESD 100-2005-ESD 100-2006-ESD 100-2007-ESD	Replacement filters MG100S Micro/gas filter, standard Micro/gas filter, MEK-application Micro/gas filter, Epoxy-application Micro/gas filter, ammonia Micro/gas filter, CO ₂
	800-1000-ESD	Filter unit MG350S, ESD-safe* Filter unit operated by electricity for fumes and gases for connection to serveral extraction arms or to a small suction cabinette. Delivered complete with remote control.
		$eq:spectral_$
	800-2000 800-2001 800-2003 800-2006 800-2007	Replacement filters MG350S Micro filter Gas filter, standard Gas filter, solvents type MEK Gas filter, ammonia Gas filter, CO ₂
	PC-UK PC-EU PC-US PC-AU	Please state which power cord you require for the units: Power cord model United Kingdom Power cord model Europé Power cord model USA Power cord model Australia

January 2005