

WXD2010N

2-Channel Solder- and Desoldering Station, 200 W (255 W)
Product no.: WXD2010N



Benefits

- › Desoldering station WXD 2, 2 channels digital and electronically controlled with desoldering iron WXDP 120
- › Soldering- and desoldering tools with intelligent WX technology
- › Compatible with WXMT-MS and WXMT desoldering tweezers
- › Intuitiva touch screen display
- › Compressed air supply required: 400 - 600 kPa (50-87 psi); oil-free, dry compressed air
- › Data logging and PC connectivity possible
- › Standby and auto off modes for energy savings
- › Peripheral control of WHP 1000 / WHP 3000 hot plates and Zero Smog 4V and 6V fume extraction units




For this purpose, we recommend:



Solder fume extractors



Soldering irons



Cleaning




Pre-heating plates



Technical Data

Dimensions L x W x H (mm)	174 x 154 x 135
Dimensions L x W x H (inches)	6,69 x 5,94 x 5,12
Weight (approx.) in kg	3.2
Voltage	120 V
Power	200 W (255 W)
Channels	2
Temperature range (depends on tool) °C	50 - 550
Temperature range (depends on tool) °F	150 - 999
Temperature accuracy °C	±9
Temperature accuracy °F	±17
Temperature stability °C	±2
Temperature stability °F	±4
Equipotential bonding socket	Via 3, 5 mm pawl socket on back of unit.
Display	255 x 128 dots / Backlighting
Air consumption l/min	35
Operating pressure in bar/psi	4,0 - 6,0 / 58 - 87
Capacity l/min	---
Vacuum	55 kPA (8 psi)

Owning the bench



PROFESSIONAL



FILTRATION



EREM



XCELITE