

VOLTAGE/CURRENT STANDARDS

YOKOGAWA

2553

2553
DC Voltage/Current Standard

255342
233 × 149 × 364 mm 8 kg
(9-1/4 × 5-7/8 × 14-3/8" 17.6 lbs)

The 2553 is an ultra-stable, high-resolution DC voltage and current source which delivers output voltages from 1 μ V to 12 V, and output currents from 0.1 μ A to 120 mA at an accuracy of $\pm 0.02\%$.

Output voltage and current are set using three dials on the front panel. Settings are controlled by digital signals passing through photocouplers and microprocessors, and are displayed on a red 5-digit LED.

The 2553 also features the five most commonly used TC ranges conforming to ANSI, DIN or JIS standard for calibrating and testing thermocouple thermometers or related devices. Corresponding emf outputs are available by selecting the relevant range and setting the temperature in $^{\circ}$ C.

The 2553 can be remotely programmed and controlled using an optional General Purpose Interface Bus (GP-IB) that meets the IEEE 488 Standard. This enables the 2553 to be interfaced easily with other instruments and to be applied in a fully automatic calibration or test system.

AVAILABLE MODELS

Model	Temperature Setting Range	Description
255341	IEC 584-1 ($^{\circ}$ C)	Standard model
255342		Standard model with GP-IB

- High accuracy of output — $\pm 0.02\%$ on all ranges
- emf output for 5 thermocouple types conforming to IEC 584-1
- Output divider from 1 to 15 divisions
The OUTPUT DIVIDER divides any voltage and current setting from 1 up to 15. This function is invaluable for

calibration, testing or adjustment of most meters of non-decade ranges.

- Non-contact output setting for long-term reliable operation
The 2553 completely eliminates switch and relay contact problems. Output voltage, current and emf are set using optical couplers.
- Easy-to-read, red LED display
- Fully protected against overload and short circuits
The maximum output voltage and current are automatically limited to prevent damage to the circuitry in the event of accidental short circuits.
- GP-IB-programmable with optional IEEE interface
The output range, polarity, voltage, current and output ON/OFF are remotely programmable to facilitate system interface.
- Optional semiconductor probe with built-in reference junction compensator

SPECIFICATIONS

Output Voltage/Current Ranges and Accuracy of Output:

Range	Output Voltage/Current	Resolution	Accuracy of Output (at $23\pm 3^{\circ}$ C)
10 V	0 to ± 12.000 V	1 mV	$\pm 0.02\%$ of range
1 V	0 to ± 1.2000 V	100 μ V	$\pm 0.02\%$ of range
100 mV	0 to ± 120.00 mV	10 μ V	$\pm 0.02\%$ of range
10 mV	0 to ± 12.000 mV	1 μ V	$\pm (0.02\%$ of range + 4 μ V)
100 mA	0 to ± 120.00 mA	10 μ A	$\pm 0.02\%$ of range
10 mA	0 to ± 12.000 mA	1 μ A	$\pm 0.02\%$ of range
1 mA	0 to ± 1.2000 mA	0.1 μ A	$\pm 0.02\%$ of range

VOLTAGE/CURRENT STANDARDS

YOKOGAWA

2553

Maximum Output and Internal Resistance:

Range	Maximum Output (approx.)	Internal Resistance (approx.)
10V	120 mA	Less than 10 mΩ
1 V	120 mA	Less than 10 mΩ
100 mV		Less than 1.5 Ω
10 mV		Less than 1.5 Ω
100 mA	12 V (0 to 50 mA) 9 V (50 to 100 mA)	1 MΩ
10 mA	15 V	1 MΩ
1 mA	15 V	10 MΩ

Output Setting: 3 dials on the front panel (opto-setting using photo-couplers),

1st and 2nd dials... 16 steps, 3rd (lowest digit) dial... 32 steps

Setting Value Indication: Red 5-digit LED display

Output Unit Marks: mV, V, mA or °C

OUTPUT DIVIDER:

DIVIDER output = output setting × n/m, m and n are selectable by OUTPUT DIVIDER dual-dial,

m ... 1, 2 through 15 in 15 uniform divisions,

n ... 0, 1 through 15 (n ≤ m)

Accuracy of Output Divider: Within ±1 digit of LSD

Temperature Coefficient: 50 ppm/°C at 5 to 40°C

Calibration Cycle: 3 months

Ripple: Less than ±0.01% of setting range on 100 mV, 1, 10 V, 10, 100 mA ranges (for DC to 60 Hz components), less than ±0.05% of setting range on 1 mA range

Common Mode Rejection (DC to 60 Hz): Approx. 120 dB for voltage output, approx. 0.1 μA/V for current output

Effect of Power Supply Voltage Fluctuation: Within ±0.02% of range against ±10% fluctuation in rated value

Overcurrent Protection: Automatically limits output current at approx. 120 mA

Overvoltage Protection: Automatically sets output voltage to zero at approx. 15 V

Polarity Selection: + or -

Insulation Resistance: More than 100 MΩ at 500 V DC between case and guard, and between power line and case

Dielectric Strength: 1,500 V AC for one minute between power line and case, 100 V AC for one minute between case and guard

Operating Temperature Range: 5 to 40°C (41 to 104°F)

Humidity Range: 5 to 95% relative humidity

Warmup Time: Approx. 30 minutes

Power Requirements: 100, 120, 200, 220 or 240 V AC (must be specified), 50 and 60 Hz

Power Consumption: 50 VA max

Accessories supplied at no extra cost: Power cord (2- or 3-prong type)... 1 set, fuses... 2 pcs

Standard	TC Type (RANGE)	Setting Range (emf output)	Accuracy (at 23±3°C)		Resolution (approx.)	Internal Resistance (approx.)
			At 25°C×n setting (n: positive integer)	At setting other than 25°C×n		
IEC 584-1	R	0 to 1000.0°C 1000 to 1768°C	±3.00°C ±3.36°C	±3.37°C ±3.76°C	1.5°C Max	1.5 Ω Max
	K	-200 to 0°C 0 to 900°C 900 to 1200°C	±0.94°C ±0.50°C ±0.70°C	±1.17°C ±0.57°C ±0.77°C	0.15°C Max	1.5Ω Max
	E	0 to 700°C	±0.35°C	±0.41°C	0.15°C Max	1.5Ω Max
	J	-200.0 to 0°C 0 to 600°C	±0.68°C ±0.47°C	±0.90°C ±0.54°C	0.15°C Max	1.5 Ω Max
	T	-200.0 to 0°C 0 to 200°C	±0.35°C ±0.21°C	±0.50°C ±0.30°C	1μV equiv.	1.5 Ω Max

Note: Compensation accuracy when used with an optional semiconductor probe: ±0.38°C (±0.76°C for R) in 0 to 50°C measuring range.

• OPTION

General Purpose Interface Bus (GP-IB)... 255342

Functional, Electric and Mechanical Specifications:

Meets IEEE Standard 488-1978 "Digital Interface for Programmable Instrumentation", interface function and identification... SH 1, AH 1, T 6, L 4, SR 1, RL 1, PP 0, DC 1, DT 1, C0

Interconnected Devices: 0 up to 15 maximum.

Notes: 1. GP-IB should always be ordered together with the standard instrument since the combination instrument will be tested at YOKOGAWA.

2. Interface cable to controller is not provided (must be prepared by user).

• OPTIONAL ACCESSORY FOR 2553

257825 Semiconductor Probe

Measuring Range: -20 to 60°C

Accuracy: ±0.3°C (with the 2553)

Insulation Resistance: More than 100 MΩ at 500 V DC between terminal tips and the 2553 ground terminal

Dielectric Strength: 100 V AC for one minute between terminal tips and 2553 ground terminal

Cord Length: Approx. 2 m (6.6 ft)

Terminal Material: Copper

Accessories Supplied: Round tips... 5 pcs